



Castrol Motorcycle Coolant

Heat Transfer Fluid

Description

Castrol Motorcycle Coolant is a pre-diluted ethylene glycol based, fully formulated, heat transfer fluid. Developed to meet the requirements of all water-cooled motorcycles and scooters.

Application

Castrol Motorcycle Coolant is recommended for all categories of motorcycles and scooters, it is not recommended for use with magnesium alloy engines.

Advantages

Castrol Motorcycle Coolant is designed to provide:

- anti-freeze performance down to -25°C
- protection against corrosion for longer engine life
- outstanding cooling and heat transfer properties
- protection of water system components
- compatibility with motorcycles paints in event of spillage

Typical Characteristics

Name	Method	Units	Castrol Motorcycle Coolant
Appearance	Visual	-	Clear, blue/green liquid
pH, Engine Coolants / Antirusts	ASTM D1287	-	8.0
Reserve Alkalinity	ASTM D1121	ml 0.1N HCl	10
Specific Gravity @ 15°C	ASTM D4052	-	1.03
Maximum freezing protection	ASTM D3321	°C	-25

Product Performance Claims

Based on coolant concentrate conforming to:
ASTM D3306(I)
BS 6580:2010

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Motorcycle Coolant

12 Jan 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com